



**Industrial Product Specification
26% CONCENTRATED CRUSHED TOMATO PASTE**

26% NTSS Hot Break Tomato Paste – Concentrated Crushed

Containers: 300 Gallon Aseptic Bag in Bin
55 Gallon Aseptic Bag in Fiber / Metal Drum

I. GENERAL

Tomato Paste shall be processed from the liquid obtained from mature, whole red tomatoes that contains no additives, and is produced in accordance with good commercial practice. The raw material shall conform in every respect to the provision of the Federal Food, Drug and Cosmetic Act and any regulations promulgated there under.

II. PRODUCT REQUIREMENTS

INGREDIENTS: Tomatoes

CHARACTERISTIC	LEVEL
<u>Chemical and Physical</u>	
Natural Tomato Soluble Solids at 20 C	26% +/- 0.5%
Consistency - Bostwick (Hot Break) (12% Total Solids 30 Sec. at 20 C Time of Pack)	<4 cm at time of pack
pH	4.3 +/- 0.2
Color (Hunter Lab Colorimeter)	45 to 50 Points, Grade A
Finish (To Customer Specifications)	.156 or .250 Screen
Defects	Meet USDA Grade A Requirements
Specific Gravity	1.1218 (~9.34lb/gal)

NOTE: All physical characteristics are packed to individual customer specifications.

<u>Microbiological</u>	<u>Commercially Sterile</u>
Bacteria	<10 CFU/gm
Mold Count (USDA-Howard Mold Count Procedure)	≤40%
Fly eggs, worms, insect fragments	Not to exceed USDA tolerance
<u>Net Weight</u> 300 Gallon Bin	2,870 lbs. +/- 30 lbs.
<u>Cube Size</u> 300 Gallon Bin	52.86 Cubic Feet

Product shelf life is a minimum of 2 years (24 months) stored @ ambient temperature.